

## HURRICANE II HEADSET



Recommended for public safety markets, manufacturing, airline industries and all users in high noise environments.

The **Hurricane II headset** is designed to provide the performance of a heavy duty headset in a high noise environment without all of the weight and bulk. The dual ear loops ship standard with NoisEz<sup>SM</sup> Ear Tips with an NRR rating of 29dB, delivering advanced protection against dangerous decibel levels. The user can easily convert the headset for use in a low noise environment by simply switching out the ear tips. The closefitting headset can be worn comfortably under a helmet or cap.

### Mechanical Specifications:

- Cable pull from T module, axial: 30 lbs
- Cable pull from headset, axial: 20 lbs
- Wire pull from receiver, axial: 20 lbs
- Receiver wire pull from headset, axial: 20 lbs
- Flex at connector: 25,000 cycles
- Cable flex at T module: 6,000 cycles
- Cable flex at headset: 15,000 cycles
- Cable flex at receiver: 5,000 cycles
- Wireform flex (tip to tip): 25,000 cycles
- 24 month manufacturer's warranty

### Electrical Specifications:

- Microphone sensitivity at 94dB SPL: -44 typical

### Environmental Specifications:

- Operating temperature: -20° C to +60° C
- Storage temperature: -40° C to +80° C

**Be clear, stay connected.**

Visit [www.ottoexcellence.com](http://www.ottoexcellence.com) or call toll-free 888-234-OTTO (6886) or direct 1-847-428-7171.



Multiple ear insert options included.

Easily converts from high noise to low noise environment.



Optional Remote Push-to-Talk styles provide hands-free operation for users driving, carrying weapons or tools, or any application where their hands may be otherwise occupied.



**Torpedo Push-to-Talk  
with 2.5 mm Pigtail**



**Ring Push-to-Talk**



**80 mm  
Push-to-Talk**



**Barrel Push-to-Talk**



**Flat Push-to-Talk**