

## **TC-508**

# Professional Two-way Radio Affordable & Reliable










- Tough & Light-weight
- Robust & Reliable
- Longer Battery Life
- Enhanced Voice Quality



## TC-508

### **Professional Two-way Radio**

## Leading Features\_

#### ■ Tough & Light-weight

TC-508 has a light-weight but exceptionally strong body, allowing it to be carried about easily and to survive harsh conditions.

#### ■ Robust & Reliable

environments of its users. It meets or exceeds the HYT 5-year ALT test.

#### ■ Longer Battery Life

TC-508 is equipped with a 1650mAh battery that enables you to transmit and receive, on a 5-5-90 basis, for up to 14 hours.

#### ■ Enhanced Voice Quality

TC-508 employs advanced voice technologies to better the sound quality during your communication.

#### **Main Functions**

**High/Low Power Switch** 

Wide/Narrow Band Switch

**Monitor** 

CTCSS/CDCSS and Squelch Tail Elimination

**Channel Scan** 

**Battery Save** 

**Low Battery Alert** 

**Busy Channel Lockout** 

**Time-out Timer (TOT)** 

**PC Programmable** 

**Wired Clone** 

**Squelch Levels Selectable** 







### **Recommended Applications**

- Hospitality
- Manufacturing
- Retail

- Education
- Construction
- Security

#### **Accessories**

Standard Accessories Li-Ion Batte Belt Clip Rapid-Rate Charger (for Li-Ion Battery

Power Adapter Antenna

#### Optional Accessories



Li-lon Battery(1300mA BL1301



Vehicle Power Adapte CHV09



Six-unit Switching Powe PS7002



Remote Speaker Microphone SM08M3



Earbud with on-MIC PTT & VOX ESM12



D-earset with in-Line MIC & VOX EHM15



D-earset with Boom MIC & VOX EHM16



Earpiece with on-MIC PTT & Transparent Acoustic Tube EAN12



Receive-Only Earpiece with Transparent Acoustic Tube (for use with remote speake microphone) ESS08



(not swivel)(black)
NCN001



Receive-Only Earpiece (for use with remote speake microphone) ESS07

**Note:** Pictures above are for reference only and may vary from actual product.

#### General

Frequency Range(MHz)	VHF: 146-174 UHF: 450-470
Channel Capacity	16
Channel Spacing(KHz)	
Operating Voltage(V)	7.4
Battery	
Battery Life (5-5-90 Duty Cycle)	14 hours
Frequency Stability(ppm)	
Operating Temperature( $^{\circ}\!\mathbb{C}$ )	-20~+65
Antenna Impedance( $\Omega$ )	
Dimensions (H $\times$ W $\times$ D)(with battery, without antenna)(mm)	113×54×35
Weight (with antenna & battery)(g)	

Power Output	5W/2W(VHF) 4W/2W(UHF)
Modulation	16K0F3E/11K0F3E
Spurious and Harmonics	≤-26dBm (<1G)
FM Noise	40/35dB
Audio Distortion	≤5 %
Modulation Limiting	≤5KHz (25KHz) ≤2.5KHz (12.5KHz)
Audio Response	≤+1~-3dB (6dB/oct pre-emphasized, 300-3000Hz)

All Specifications are tested according to applicable standards, and subject to change without notice due to continuous development.

Sensitivity	≤0.251uV/0.282uV
Adjacent Channel Selectivity	65dB/55dB
Intermodulation	
Spurious Response Rejection	65dB
S/N	45dB/40dB
Rated Audio Power Output	0.5W(Speaker impedance: 16 Ohm)
Rated Audio Distortion	
Conducted Spurious Emission	-57dBm < 1GHz -47dBm > 1GHz









#### **Hytera Communications Corporation Limited**

Address: HYT Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China Http://www.hytera.com Stock Code: 002583.SZ

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

Your Local Dealer